## **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



#### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

H04Q 7/04, H04B 7/26

A1

(11) International Publication Number: WO 92/19078

(43) International Publication Date: 29 October 1992 (29.10.92)

SE

(21) International Application Number: PCT/SE92/00227

(22) International Filing Date: 8 April 1992 (08.04.92)

(30) Priority data: 9101105-6 12 April 1991 (12.04.91)

(71) Applicant (for all designated States except US): COMVIK GSM AB [SE/SE]; P.O. Box 123, S-126 23 Hägersten (SE).

(72) Inventor; and

z

(75) Inventor/Applicant (for US only): JULIN, Tomas [SE/SE]; Andvägen 32, S-184 61 Åkersberga (SE).


(74) Agent: AWAPATENT AB; Box 45086, S-104 30 Stockholm (SE).

(81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FI, FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), MC (European patent), NL (European patent), NO, SE (European patent), US.

Published

With international search report.

(54) Title: METHOD IN MOBILE TELEPHONE SYSTEMS IN WHICH A SUBSCRIBER IDENTITY MODULE (SIM) IS ALLOCATED AT LEAST TWO IDENTITIES WHICH ARE SELECTIVELY ACTIVATED BY THE USER



abstrac.

Method in mobile telephone systems, especially of the GSM type, in which a subscriber identity module (SIM) is allocated at least two identities (IMSI 1, IMSI 2) which are selectively activated by the user. A preferred embodiment of a subscriber identity module consists of an active card which can be inserted in two different positions corresponding to one and the other identity, respectively. Preferably, the positions pertain, respectively, to one and the other end of the card

#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT:	Austria	FI	Finland	MI	Malı
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NI.	Netherlands
BC	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	RO	Romania
	Canada	iT	Italy	RU	Russian Federation
CA		J₽	Japan	SD	Sudan
CF	Central African Republic	jr Li	the contract of the contraction	SE	Sweden

CS	Czechosiovaki	J.	Sect affilia		
DE	Cormany	LU	Luxembout <sub>e</sub> ,	i ·	ited States Analysis
DK	Denmark	MC	Monaco		
E.c.	Co. in	MG	Madagascar		

WO 92/19078

METHOD IN MOBILE TELEPHONE SYSTEMS IN WHICH A SUBSCRIBER IDENTITY MODULE (SIM) IS ALLOCATED AT LEAST TWO IDENTITIES WHICH ARE SELECTIVELY ACTIVATED BY THE USER

#### Field of the Invention

The present invention relates to telephone systems,

5 preferably mobile telephone systems, in which the subscriber units, preferably mobile units or stations, are
controlled by a subscriber identity module. More specifically, the invention concerns a method in such a telephone system, wherein the subscriber identity module is

10 utilised in a new way, as well as a subscriber identity
module especially suited for use in connection with the
method.

The invention is advantageously applied to a telephone system of the GSM type (Global System for Mobile

Communication). Although the invention is by no means
restricted to such an application, it will be described
hereinafter with reference to a system of this type.

Background of the Invention

phone system which is not geographically confined to a single country. A subscriber may use any subscriber unit (Mobile Station - MS) by controlling it with the aid of a subscriber identity module (SIM), which may be an active card or a plug-in unit inserted in the subscriber unit and producing the subscriber's identity (IMSI) which is allocated to a directory number (Mobile Station International ISDN number - MSISDN). Information on IMSI and MSISDN is stored, together with other information relating to the subscriber, in a home database (Home Location Register - HLR) with the operator of the network including the subscriber. The system comprises visitor databases (Visitor Location Register - VLR) and switches (Mobile Services

ing to the area of location of the subscriber unit MS.

20

Since the above concepts, as well as the design and operation of the system as a whole, are subjected to extensive standardisation, no detailed description seems required here.

Systems of the above type are widely used for service calls, but also to some extent for private calls. Distributing the costs for service and private calls usually cause problems or involves extra work.

One and the same subscription can also be used by

different people, e.g. within one and the same company.

Also in this case, distributing the costs among the different people concerned may cause problems or involve extra work.

#### Object of the Invention

The object of the present invention is to eliminate the above inconveniences and also in other respects enable a more flexible use of subscriptions and subscriber identity modules.

## Summary of the Invention

with the steel was

This object is achieved by a method and a subscriber identity module having the distinctive features recited in the appended claims.

The invention is thus based on the insight that a subscriber identity module can be allocated at least two different identities which are selectively activable by the user. As will be appreciated, there may be two identities, e.g. a service identity and a private identity, which belong to the same user, which seems to be the currently preferred case. However, different identities might also be used, which correspond to several potential users of the subscriber identity module.

Preferably, only one identity can be activated at a

<sup>35</sup> new identity can be regarded as activated. The associated home database is suitably made to store information on

which identity is activated, so that calls can be set up, cost information stored and so forth in a correct way.

The subscriber identity module can be so designed that the selective identity activation, i.e. the selection of identity function in the subscriber identity module, can be carried out with the aid of keys or the like provided on the subscriber unit, or with the aid of special means provided on the subscriber identity module, e.g. so-called touch contacts when the module is an active card.

The activation may then, for instance, take place in connection with the input of a so-called PIN code. In that case, each identity can be allocated a special code. This means that a number of different users (corresponding to the number of different identities) can share the sub-

scriber identity module employed. It is also possible to have a user's PIN code supplemented with code elements for selecting the desired identity (for instance, service or private).

In a preferred embodiment of the subscriber identity

20 module according to the invention, the module is an active
card designed to be inserted in the subscriber unit in two
different positions, preferably with one or the other end
first, each position corresponding to an allocated identity. This enables an embodiment in which each identity

25 function is clearly marked on the card, which thus becomes
easy to handle. A change of identity is performed simply
by taking out the card and then again inserting it, now in
the other position, e.g. when switching from a service
call to a private call, or vice versa.

30 It will be appreciated that the subscriber identity module according to the invention may be provided with specially programmed circuits which contain either interested identity for the contains and contains and contains and contains are contains as a contain and contains and contains are contains as a contain and contains and contains are contains as a contains a contain and contains are contains and contains are contains and contains are contains and contains and contains are contains and contains are contains and contains and contains are contains and contains are

provision of a first circuit at one end of the card and a second circuit at the other end of the card, all in com-

pliance with current standards for such cards in respect of the positioning of the contact means, and so forth. Thus, one side of the card is able to identify one identity, while the other side identifies the other identity.

As to the allocation of directory numbers in a home database, there are different alternatives in accordance with the invention.

In a first alternative, the different identities of the subscriber identity module are allocated to one and 10 same directory number. The home database is designed to set up calls against and register cost information etc. for the current combination of directory number and identity. For properly performing this, the home database should be informed of which identity is activated. This 15 can be done in that only one identity can be activated at a time, so that when a 'new' identity is activated, the preceding identity is always deactivated and the home database informed thereof. Such deactivation may, for instance, be performed by using a function of the type 20 'Cancel IMSI', which is employed in GSM-type systems. Such deactivation means that information on this identity is cancelled from the visitor database employed, and that the home database is always informed when the identity is again activated.

An incoming call is set up against the activated identity, controlled by the information in the home database.

If there is no information on the activated identity, an incoming call can first be set up against a selected identity among the possible identities. If the selected identity is found to be non-activated, the call can be transferred so as to be set up against the next possible

25

ಚಿಕ್ಕಾರ ಕಟ್ಟಿಕು

modify the function of his home database without coming

into conflict with the standard of e.g. a system of GSM type.

In a second alternative, the different identities of the subscriber identity module are each allocated to a unique directory number. Of these directory numbers, one particular number is the subscriber's external telephone number, while the other number(s) is (are) only used in the home database and may be unknown to the subscriber and to the public. It is convenient also in this case that only one identity can be activated at a time and that the home database is informed thereof, e.g. as in the first alternative.

When there is an outgoing call, the selected and activated identity is used together with the allocated directory number in conventional manner.

Incoming calls are always set up against the identity allocated to the special directory number, provided that this identity is activated. If not, the call can be transferred to the subscriber's next directory number with associated identity. It will be appreciated that this transfer can be performed directly, without the call being set up against the first-mentioned identity, if the home database knows which identity is activated.

For call transfer, use may, according to the invention, advantageously be made of a function of the type 'Call Forwarding Unconditional' (CFU), which is a well-known standard function adapted to be controlled by the subscriber. By adding a corresponding function, controlled by the network operator, to the home database, one or more of the subscriber's directory numbers can be supplemented for direct transfer in the event of the associated identity being non-activated and provided that the subscriber

ment of the second alternative, which is a further developdirectory numbers are external telephone numbers, of which one suitably is a service number and the other is a private number. Informing of the activated identity and the direct call transfer can be performed as in the second alternative.

- Thus, it will be appreciated that the present invention provides several different options for a subscriber as to different identities and amounts of external telephone numbers, while using a single subscriber identity module.
- The invention will be illustrated in more detail below with the aid of non-restricting embodiments, reference being made to the accompanying drawings.

## Brief Description of the Drawings

- Fig. 1 is a highly schematic diagram illustrating an embodiment of the invention,
  - Fig. 2, which is a diagram similar to that of Fig. 1, illustrates another embodiment of the invention.
- Fig. 3 is a highly schematic diagram illustrating the information flow occurring when an identity is activated and deactivated in accordance with an embodiment of the invention,
  - Fig. 4 illustrates a supplementary addition to a home data base in accordance with an embodiment of the invention,
- Fig. 5 is a flow chart illustrating a mode of using a 'Call Forwarding Unconditional' function in accordance with the invention, and
- Fig. 6 is a schematic top plan view of an active card modified for use as a subscriber identity module in accord-30 ance with an embodiment of the invention.

# Description of the Preferred Embodiments

راك رقير

Fig. 1 schematically illustrates how an embodiment of

visitor database VLR communicate with one another, as indicated by the arrows 1 and 3. The visitor database VLR is in wireless communication with the mobile station MS,

which is controlled by a SIM card which is activable to give the identity IMSI 1 or the identity IMSI 2. The directory number MSISDN corresponds to these identities. Information on MSISDN and the linkage to the two identities ties IMSI 1 and IMSI 2 are stored in the home database HLR.

When IMSI 1 or IMSI 2 is activated by means of the SIM card in the mobile station MS, information thereon is signalled to the home database HLR, which transmits information on the current combination MSISDN-IMSI 1, or MSISDN-IMSI 2, to VLR in customary manner. Then, the call is set up in the usual way in consideration of the selected combination.

Fig. 2 schematically illustrates another embodiment

of the invention, in which each identity IMSI 1 and IMSI 2

is allocated to a directory number MSISDN 1 and MSISDN 2,

respectively, which both are external telephone numbers.

For the activated combination MSISDN-IMSI, the call is set up etc. in customary manner.

Fig. 3 illustrates the essential steps in the information flow that may be used for ensuring that the home database HLR is informed of which of the identities IMSI 1 and IMSI 2 is activated.

In the initial position (at the top), IMSI 1 is

25 assumed to have been activated by the insertion of the SIM card with one end first into the mobile station. Now, the user pulls out the card and inserts it again with the other end first in order to activate IMSI 2. Then, IMSI 2 is signalled to the visitor database VLR which, noting

30 that the IMSI is a non-registered one, transmits updating signals to the home database HLR, which stores information on IMSI 2 being activated, and deactivates IMSI 1 by

mobile station MS. Thereafter, data on IMSI 2 is transmitted to the visitor database. The call can now be set up

5

by using the combination MSISDN 2-IMSI 2. When the user once again turns the SIM card, i.e. changes identities, a corresponding activation of IMSI 1 and a corresponding deactivation of IMSI 2 take place.

When there is an incoming call to the directory number whose identity is not activated, the call is transferred directly to the other directory number by using 'Call Forwarding Unconditional'. To this end, the home database is extended with one field for each directory 10 number, as illustrated in Fig. 4. The added field is the one at the very bottom. For MSISDN 1 is here entered: call transfer to MSISDN 2, and vice versa. The call transfer in accordance with these added fields takes place on condition that the user has not himself initiated any transfer 15 of this kind, which in that case would appear from the field immediately above.

The entry of the additional fields of the home database is conveniently carried out simultaneously with the signalling sequence according to Fig. 3. The entry is 20 exemplified in the flow chart of Fig. 5.

Thus, the 'Call Forwarding Unconditional' can be implemented only if the subscriber has not himself requested such call transfer to another number. In other words, the subscriber may still use this subscriber ser-25 vice as usual. If he does not, the home database HLR will transfer an incoming call from the non-activated combination MSISDN-IMSI to the combination as last activated and registered.

Thus, it will be appreciated that the subscriber has 30 several different options: one or two external telephone numbers; automatic transfer of service calls to the private number, and vice versa; or other personally-con-

nema:...

that has been modified in accordance with the invention so as to provide two identity functions. At one end, the card 11 is equipped in conventional manner with a circuit so as

5

9

to provide a first identity function when inserted into a mobile station, as indicated by the arrow 15. The illustrated side of the card may be a service side and have a suitable and clear marking to this effect.

The other side of the card is the private side. For this purpose, a second, completely separate circuit 17 is provided at the other end of the card and on the private side, in accordance with current standards for the arrangement of circuits and contacts. When the private 10 side is to be used, the card is inserted with said other end first, as indicated by the arrow 19 on the private side. This side may also have a suitable and clear identity marking.

15

20

25

30

#### CLAIMS

- 1. Method in telephone systems, preferably mobile

  5 telephone systems, especially of the GSM type, in which
  subscriber units (MS) are controlled by a subscriber
  identity module (SIM), characterised in
  that the subscriber identity module (SIM) is allocated at
  least two identities (IMSI 1, IMSI 2) which are selectively usable, the user selectively activating the desired identity when using a subscriber unit (MS).
- 2. The method of claim 1, in which the subscriber identity module (SIM) is of the active-card type, c h a r a c t e r i s e d in that use is made of a subscriber identity module (SIM) which has double identity functions and is so designed that one identity (IMSI 1) is utilised when the module (SIM) is inserted in the subscriber unit (MS) in a first position, especially with one end first, and that the other identity (IMSI 2) is utilised when the module (SIM) is inserted in the subscriber unit (MS) in a second position, especially with the other end first.
- 3. The method of claim 1, c h a r a c t e r i s e d in that use is made of a subscriber identity module (SIM) which has at least two identity functions, the desired identity being selectively activated with the aid of the keys of the subscriber unit (MS) or with the aid of activating means provided on the subscriber identity module.
- 4. The method of claim 3, characterised in that the desired identity is activated in connection with the input of a PIN code.
- 35 IMSI 2) of the subscriber identity module (SIM) are allocated to one and the same directory number (MSISDN), an incoming call being set up against one or the other iden-

tity (IMSI 1 or IMSI 2), controlled by the subscriber's home database (HLR) in response to the selective identity activation.

- 6. The method of claim 5, characteris5 ed in that an incoming call is first set up against one identity (IMSI 1) and, if this identity is found to be non-activated, then against the other identity (IMSI 2) by call transfer.
- 7. The method of any one of claims 1-4, char10 acterised in that the identities (IMSI 1, IMSI 2)
  of the subscriber identity module (SIM) are each allocated
  to a directory number (MSISDN 1 and MSISDN 2, respectively).
- 8. The method of claim 7, c h a r a c t e r i s 15 e d in that one directory number (MSISDN 1) is the subscriber's external telephone number, an incoming call
  being transferred to the other directory number (MSISDN 2)
  when the identity (IMSI 1) allocated to the telephone number is not activated.
- 9. The method of claim 7, characterised in that the directory numbers (MSISDN 1, MSISDN 2)
  are external telephone numbers of the subscriber, e.g. a
  service telephone number and a private telephone number,
  an incoming call to a directory number (MSISDN 1 or MSISDN
  25 2) whose allocated identity (IMSI 1 and IMSI 2, respectively) is not activated, being transferred to the other
  directory number (MSISDN 2 or MSISDN 1).
- 10. The method of claim 6, 8 or 9, c h a r a c t e r i s e d in that the call transfer relies on a func30 tion of the type 'Call Forwarding Unconditional", provided that this function has not been used by the subscriber.
  - 11. The method of any one of the preceding claims,

e d in that, when one identity (IMSI 1 or IMSI 2) is selectively activated, involving a change of identity, the

previous identity is deactivated, controlled by the subscriber's home database (HLR).


- 13. Subscriber identity module (SIM) for use in connection with a subscriber unit in a telephone system, preferably a mobile telephone system, especially of the GSM type, c h a r a c t e r i s e d in that it includes at least two identity functions which are selectively activatable.
- 14. The subscriber identity module of claim 13,

  10 characterised in that it is of the activecard type and is designed for insertion into the subscriber unit in two different positions, preferably relating,
  respectively, to one and the other end of the card, one
  position allowing activation of a first identity (IMSI 1)

  15 and the other position allowing activation of a second
  identity (IMSI 2).
- 15. The subscriber identity module of claim 14, c h a r a c t e r i s e d in that it is provided with two separate circuitries, of which one is allocated one identity (IMSI 1) and the other is allocated the other identity (IMSI 2).

25

30








FIG.4





# INTERNATIONAL SEARCH REPORT

International Application No PCT/SE 92/00227

	ASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ding to International Patent Classification (IPC) or to both National Classification and IPC		
	: H 04 Q 7/04, H 04 B 7/26		
II. FIE	LDS SEARCHED ,		
	Minimum Documentation Searched  Classification Symbols		
Classifi	cation System Classification Symbols		
IPC5	H 04 B, H 04 Q, H 04 M		
	Documentation Searched other than Minimum Documentation to the Extent that such Documents are included in Fields Searched <sup>8</sup>		
SE,DK	s,FI,NO classes as above		
III. DO	CUMENTS CONSIDERED TO BE RELEVANT®		
Categor		Relevant to Claim No. <sup>13</sup>	
A	DE, B2, 2147638 (TOYOTA MOTOR SALES CO.,LTD.) 23 January 1975, see column 1, line 54 - column 2, line 31		
A	US, A, 3581019 (DONALD P. RYAN ET AL) 25 May 1971, see the whole document	1-15	
A	US, A, 4734928 (SHELDON WEINER ET AL) 29 March 1988, see column 3, line 17 - line 32	1-15	
A	US, A, 4868846 (YRJÖ KEMPPI) 19 September 1989, see the whole document 	1-15	
"A" d	cial categories of cited documents: 10  Incomment defining the general state of the art which is not considered to be of particular relevance  Incomment defining the general state of the art which is not considered to be of particular relevance  Incomment defining the general state of the art which is not cited to understand the principal cited to understand the principal cited to understand the principal cannot be considered according to the con	ce, the claimed invention	
"O" d	locument which may throw doubts on griority claim(s) or which is cited to establish the publication date of another size and the special reason (as specified)  document referring to an oral disclosure, use, exhibition or wither means  in the srt.	e an inventive step when the or more other such docu- obvious to a person skilled	
1:	locument published prior to the international filing date but "&" document member of the same aler than the priority date claimed	patent family	
	ITIFICATION  DE Acto - Indicess Sel 465		
	- tgg:		
internati	onal Searching Authority Signature of Authorized Officer Lans Hermium		
NAT.	SWEDISH PATENT OFFICE Lars Henriksson  (ISA/210 (second sheet) (January 1985)		

Category *	JMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No	
4	EP, A2, 378450 (TECHNOPHONE LIMITED) 18 July 1990, see column 3, line 53 - column 4, line 12	1-15	
	US, A, 4399330 (ROLAND KUENZEL) 16 August 1983, see the whole document	1-15	

# ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 92/00227

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 01/07/92. The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

ci	Patent document ted in search report	Publication date		t family nber(s)	Publication date
DE-B2-	2147638	75-01-23	FR-A- GB-A-	2109822 1366372	72-05-26 74-09-11
US-A-	3581019	71 <b>-05-2</b> 5	NONE		
US-A-	4734928	88-03-29	US-A-	4677653	87-06-30
US-A-	4868846	89-09-19	EP-A- JP-A-	0301740 1106533	89-02-01 89-04-24
EP-A2-	378450	90-07-18	NONE		
US-A-	4399330	83-08-16	AT-E-T- AU-B- AU-D- DE-A- EP-A-B- JP-A-	10795 552184 7508381 3034066 0047524 57080841	84-12-15 86-05-22 82-03-18 82-04-15 82-03-17 82-05-20